

OLYMPUS®



EVIS EXERA XENON LIGHT SOURCE
OLYMPUS CLV-160

POWERFUL PRECISION ILLUMINATION

Assures clear, accurate observation even of distant points thanks to powerful 300W xenon lamp coupled with an improved condenser design that achieves nearly 30% more light intensity than its predecessor, the CLV-U40



Primary Features for Powerful Performance

- Powerful 300W xenon lamp for Olympus color CCD videoscope system.
- New and improved condenser design helps achieve nearly 1.3 times as much light intensity as the CLV-U40.
- Illumination capability to cover even more distant points assures sufficient brightness when retroflexing the scope tip, observing the lower esophagus, and more.
- Improvement in light adjustment levels helps maintain appropriate brightness even when observing at extremely close range or observing the gastric angulus from directly in front.
- 35% reduction in overall size compared to its predecessor, with width reduced by a full 80 mm, saving space in your endoscopy suite.
- Simple membrane switches and clear indicators on the front panel for improved operability.
- Compatible with conventional Olympus color CCD videoscopes and fiberscopes.




Specifications

Automatic brightness control	Automatic brightness control method	Servo-diaphragm method	
Air feeding	Automatic exposure	17 steps	
Water feeding	Pump	Diaphragm pump	
	Pressure switching	4-level switching by switches (" OFF " " L " " M " " H ")	
Indicators on front panel	Method	Air pressurization or detachable water container	
	Emergency lamp	Reports absence of emergency lamp, disconnection and use of emergency lamp.	
Setting memory	Filter	Identifies a special-purpose filter setting.	
		Settings (except filter setting) are stored by an internal battery even when the power is turned OFF.	
Illumination	Lamp	Xenon short-arc lamp (ozone-free) 300 W	
	Average lamp life	Approx. 500 hours on continuous use (On intermittent use, the lamp life may vary slightly.)	
	Ignition method	Switching regulator	
	Brightness adjustment	Light-path diaphragm control	
	Cooling	Forced-air cooling	
	Color conversion	Possible by using exchangeable filter	
	Emergency lamp	Halogen lamp 12 V 100 W	
	Average emergency lamp life	Approximately 100 hours	
	Classification (medical electrical equipment)	Type of protection against electric shock	Class I
		Degree of protection against electric shock of applied part	Type BF applied part (The applied part where classification types are not marked is Type BF applied part.)
Power supply	Voltage	NTSC 100–120 V AC, PAL 220–240 V AC	
	Frequency	50/60 Hz	
	Input current	NTSC 5 A, PAL 3 A	
Size	Dimensions	370 (W) X 135 (H) X 420 (D) mm	
	Weight	15 kg	


Olympus business areas



Medical and health-care area



Imaging and information area



Industrial applications area

OLYMPUS
FOCUS ON LIFE

<http://www.olympus.com>

OLYMPUS OPTICAL CO., LTD.

San-Ei Building, 22-2, Nishi Shinjuku 1-chome, Shinjuku-ku, Tokyo, Japan

OLYMPUS OPTICAL CO. (EUROPA) GMBH.

Postfach 10 49 08, 20034 Hamburg / Wendensstrasse 14-16, 20097 Hamburg, Germany

OLYMPUS AMERICA INC.

2 Corporate Center Drive, Melville, N.Y. 11747-3157, U.S.A.

OLYMPUS KEYMED

Keymed House, Stock Road, Southend-on-Sea, Essex SS2 5QH, England

OLYMPUS SINGAPORE PTE LTD.

491B River Valley Road #12-01/04, Valley Point Office Tower, Singapore 248373

OLYMPUS BEIJING REPRESENTATIVE OFFICE

Rm. 818, South Tower, Beijing Kerry Centre, No.1 Guanghua Road, Chaoyang District, Beijing, 100020, China

OLYMPUS MOSCOW LIMITED LIABILITY COMPANY

117071, Moscow, Malaya Kaluznyskaya 19, bld. 1, fl.2, Russia

OLYMPUS AUSTRALIA PTY. LTD.

1/104 Ferntree Gully Road, Oakleigh, VIC 3166, Australia